UDP Receiver Tag Values Connector

Tag Data Exchange using UDP protocol

- Name: **TTagsReceiver**
- Version: 1.0.0.7
- Protocol: Proprietary
- Interface: TCP/IP
- Runtime: .NET 2.0 (Multiplatfrom)
- Configuration:
  - Devices / Protocols

Nodes Configuration
Points Configuration
Driver Revision History

Overview

There are 2 independent ways to use this protocol, using a TagProvider or as a DeviceChannel in the Module Device.

- **TagProvider**: allows to use of the PLC addresses directly without creating any Tags nor mappings in the Project.
- **DeviceChannel**: create Project Tags and map to the PLC addresses, allowing more control over names and data blocks. Use the Solution Import Tags Reference to setup automatically the mapping.

Communication Driver Information	
Driver name	TTagsReceiver
Assembly Name	T.ProtocolDriver.TTagsReceiver
Assembly Version	1.0.0.7
Available for Linux	False
Devices supported	N/A (Not Applicable)
Manufacturer	N/A (Not Applicable)
Protocol	Proprietary over UDP
PC Requirements	Ethernet port

Nodes Configuration

Station Configuration

Not used.

Points Configuration

Address

String field.

Driver Revision History

TTagsReceiver Revision History	
Version	**Notes**
1.0.0.7	Initial release on new documentation standards.

In this section...
