Expander Control Reference

Container that shows or hides its content with a single header click.

The **Expander** control belongs to the *Viewer* category and runs on the *P ortable* rendering target. Place it on a Display from the Components Panel and configure the properties listed below.

Properties

Properties

Property set generated from FrameworX 10.1.5.

Property	Type	Default	Description
`Left`	`Double`	0	X position from left edge *(unit: pixels)*
`Top`	`Double`	0	Y position from top edge *(unit: pixels)*
`Width`	`Double`	100	Element width *(unit: pixels)*
`Height`	`Double`	100	Element height *(unit: pixels)*
`CollapsedWidth`	`Double`	120.0	*(no description in schema)*
`CollapsedSize`	`Object`	*(none)*	*(no description in schema)*
`OriginalSize`	`Object`	*(none)*	*(no description in schema)*
`EnableScrollBar`	`Boolean`	*(none)*	*(no description in schema)*
`Settings`	`String`	*(none)*	*(no description in schema)*
`LinkedValue`	`String`	*(none)*	Tag binding expression (e.g., '@Tag.Temperature', '@Tag.Motor.Speed'). On ComboBox in DataTable/FK mode, receives the SelectedValuePath column value from the selected row.
`LabelLink`	`String`	*(none)*	Label/caption text — static string or tag expression (e.g., 'Temperature' or '@Tag.Description')
`LabelMethodList`	`String`	*(none)*	*(no description in schema)*
`LabelPreviewMode`	`Enum`	0	Design-time label preview (LinkedTags, Placeholder, Whitespace)
`Localize`	`Boolean`	False	Enable runtime text localization (true/false)
`HeaderHeight`	`Double`	26.0	*(no description in schema)*
`ContentHeight`	`Double`	100.0	*(no description in schema)*
`Background`	`Color`	*(none)*	Background color (#AARRGGBB). Themed by default — OMIT to use theme.
`Foreground`	`Color`	*(none)*	Text/foreground color (#AARRGGBB). Themed by default — OMIT to use theme.
`BorderBrush`	`Color`	*(none)*	Border color (#AARRGGBB).
`BorderThickness`	`String`	*(none)*	Border thickness (single value or 'left,top,right,bottom').

In this section...